



UNYTOUCH
MANUFACTURING

10.4" Chassis LCD Monitor

U14-OC104



Brightness
350 cd/m²

Contrast
Ratio
300:1

Viewing
Angle
70°/70°(H/V)

Response
Time
15ms (GTG)

Display
Resolution
800 x 600

Unytouch Manufacturing is proud to present a completely redesigned family of industrial panel mount monitors.

Addressing key drivers such as performance, durability and cost, the Unytouch panel mount monitors are well suited for both industrial and OEM applications.

Featuring high bright, wide viewing angle industrial LCD modules along with the ability to add touch functionality, the Unytouchpanel mount monitor makes the most of your digital world.

KEY FEATURES

- High Bright LCDs
- SVGA Resolution (800 x 600)
- Rear Mounted OSD Control
- VESA Mount
- Speakers
- 3 Year Warranty

TOUCH PART NUMBERS

- U14-OC104UR (5 Wire Resistive)
- U14-OC104UC (Capacitive)

PANEL

Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD Panel
Pixel Arrangement	RGB vertical stripe
Glass Surface	Anti-Glare coating
Pixel Number	800(H) x 600(V)
Pixel Pitch	0.264(H) mm x 0.264(V) mm
Display Size	10.4" viewable diagonal area
Active Area	211.2(H) x 158.4(V) mm
Color Depth	262K Colors
Light Source	Long life, 50,000 hours (typ)
Brightness	350 cd/m2
Contrast Ratio	150:1
Touch Technology	5 Wire resistive
Touch Interface	USB
Viewing Angle	Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)

INPUT SIGNAL

Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
Sync	Composite Sync
Frequency	Fh: 30 - 82 KHz, Fv: 60 - 75KHz

RESOLUTION

Supported	1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz
Recommended	800 x 600 @ 60 Hz

CONTROL

Front Panel Winsticker (OSD)	Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall
------------------------------	---

POWER

Input Voltage	AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A
Power Rating	Operation: 25 Watt, Off: < 5 Watt

OPERATING CONDITION

Temperature	-10°C ~ 65°C
Humidity	10% ~ 90% (no condensation)

STORAGE CONDITION

Temperature	-30°C ~ 70°C
Humidity	10% ~ 90% (no condensation)

OTHER

Audio	2W x 1 Speaker
Dimensions (W x H x D)	264 x 225 x 40.5 mm
Weight (Net/Gross)	3 Kg/4Kg
Options	Video-In: 1 x RCA Connector, 1 x S-Video
Certification	FCC, CE